

Link AX Technical Specifications

PROTOCOL SUPPORT	
Network Protocols	TCP/IP, UDP, HTTP, DHCP, NTP, SSL, IGMP
NETWORK	
Ethernet	4x 1Gbps Ethernet Ports 1x 2.5Gbps Ethernet Port
Modem	USB 2.0
WiFi	2x2 2.4GHz MU-MIMO OFDMA 802.11 b/g/n/ax, max 20dBm per chain 2x2 5GHz MU-MIMO OFDMA 802.11 a/n/ac/ax, max 20dBm per chain Frequency Range 2.412~2.472GHz, 5.180~5.825GHz
Encryption	802.11AX, 802.1x, 802.11i, WPA2, WPA and WEP 64/128 TKIP 128bit AES
POWER	
Power Input	2-pin locking connector: 12-28V
Power Consumption	17.5W (Max)
PoE	Supports IEEE 802.3at 48~56V
Battery Plates	Integrated Gold or V-mount battery plate (optional)
PHYSICAL ATTRIBUTES	
Dimensions	7.3" W x 5.7" D x 2" H [185mm x 145mm x 51mm]
Weight	Without battery plate: 37oz (1046g) With battery plate: 38.4oz (1090g)
Construction	Milled Aluminum
Mountability	2x 1/4"-20 threaded holes 1x 3/4"-16 threaded hole
INTERFACES	
Configuration Interface	Feature-rich web UI for configuration and control
Switches	On/Off, Reset, and Reboot switches

Status LEDs	Multiple LEDs for device, wireless, and network statuses
ENVIRONMENTAL	
Temperature	Operating: -10°C to 50°C Storage: -40°C to 90°C
Humidity	Operating: 5% to 95% Storage: Max. 90%